VertiLine3D - Rack Mount DC Power Supply

Rev. DSVertiLine3D - 07182012

Overview

Altronix Vertiline3D Rack Mount DC Power Supply provides eight (8) filtered and electronically regulated power outputs in a space saving 1U EIA 19" rack mount chassis. This unit is available with 24VDC power outputs. Vertiline Rack Mount DC Power Supplies are also available in sixteen (16) outputs.

VertiLine3D

Specifications

Input:

- 115VAC 60 Hz, 1.5 amp input.

Output:

- 12VDC outputs rated @ 8 amp total current max. *(1.0 amp per device, 2.5 amp max.).*
- Eight (8) PTC protected power outputs.
- Filtered and electronically regulated.

Electrical:

- Operating temperature: -20º C to 49º C ambient.
- 51.18 BTU/Hr.
- System AC input VA requirement: 172.5VA.

Mechanical:

- Units can be rack, wall or shelf mounted.

Mechanical *(cont'd)*:

- Modular 1U standard EIA 19" rack mount chassis
- Enclosure Dimensions (H x W x D approx.): 1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm)
- Product weight (approx.): 6.95 lbs. (3.15 kg.).
- Shipping weight (approx.): 8.05 lbs. (3.65 kg.).

Features:

- Eight (8) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

Agency Approvals

CE European Conformity

Enclosure Dimensions *(H x W x D) (approximate)*:

1.625” (41.275mm) x 19.125” (486mm) x 8.5” (216mm)